

## MAXCALRC - R (Macro) >> BONDED

### Special Brown Fused Aluminum

MAXCALRC is a special brown fused aluminum oxide developed for high performance abrasive products. The grits are ceramic coated, which provides an increase in the specific surface of the abrasive grain and a better adhesion between the abrasive grain and resin. MAXCALRC is low titania content product, heat treated in a rotary kiln at high temperatures and magnetic treated. These procedures guarantee low iron content and excellent stability. Produced according to ANSI or FEPA-F.

#### General Characteristics

True Specific Gravity	Friability (ANSI-B74.8R2007)
3.94 g/cm <sup>3</sup>	54%

#### Chemical Analysis by XRF (%)

Al <sub>2</sub> O <sub>3</sub>	TiO <sub>2</sub>	SiO <sub>2</sub>	Fe <sub>2</sub> O <sub>3</sub>
97.68	1.23	0.52	0.14

#### Bulk Density (g/cm<sup>3</sup>)

Grit Size	(R) cubic
10	1.92
12	1.92
14	1.92
16	1.92
20	1.92
22	1.92
24	1.89
30	1.89
36	1.86
40	1.87
46	1.84
54	1.81
60	1.79
70	1.77
80	1.74
90	1.72
100	1.69
120	1.68
150	1.67
180	1.63
220	1.60

FEPA 44 - 1:2006